

Health	1
Flammability	0
Reactivity	0
Personal Protection	В

Trebla 8417 Chapin Industrial Drive St. Louis, MO 63114 Phone 1-800-325-4404

November 4, 1998

MATERIAL SAFETY DATA SHEET

SECTION I - General Information

Product Name: Trechrome-6 First Developer Replenisher

Catalog Number: 20DE200, 20DE220, 20DE260

Formula: Aqueous Solution

SECTION II - Product and Hazardous Ingredients Information

CV	$D \Lambda$
SA	KΑ

<u>ITEM</u>	CAS#	PERCENT	PEL	RQ / TPQ
Potassium Sulfite	10117-38-1	10-15	N/A	N/A N/A
Potassium Iodide	7681-11-0	1-5	N/A	N/A N/A
Potassium Hydroxide	1310-58-3	1-5	N/A	N/A N/A
Potassium Carbonate	584-08-7	5-10	N/A	N/A N/A
Sodium Bicarbonate	144-55-8	5-10	N/A	N/A N/A
Hydroquinonesulfonic Acid,				
Potassium Salt	21799-57-1	5-10	N/A	N/A N/A
Water	7732-18-5	N/A	N/A	N/A N/A

SECTION III - Physical Data

BOILING POINT: >212° F **VAPOR PRESSURE (mmHg):** ~ 17.0 **VAPOR DENSITY (mmHg):** ~ 0.6 **SOLUBILITY IN WATER:** Complete

SPECIFIC GRAVITY: 1.31 pH: ~ 9.7

PERCENT VOLATILE BY WEIGHT: ~ 71 % EVAPORATION RATE: N/A

APPEARANCE AND ODOR: Light yellow, odorless.

SECTION IV - Fire and Explosion Hazard Data

Flash Point: None Flammable Limits: LEL: N/A UEL: N/A

Extinguishing Media: Use method appropriate for surrounding fire.

Special Fire Fighting Procedures: Use self-contained breathing apparatus and protective clothing to prevent

contact with skin and eyes.

Unusual Fire and Explosions Hazards: When heated to decomposition, it can emit toxic fumes of K₂O, SO_X, and I⁻.

SECTION V - Health Hazard Data

TLV (ACGIH): Potassium Hydroxide, 2 mg/m3.

Effects of Overexposure:

Inhalation: Expected to be a low hazard under normal conditions.

Eyes: Contact can cause irritation and possibly burns. **Skin:** Repeated and prolonged contact may cause irritation. **Ingestion:** Do not take internally. Harmful if swallowed.

Carcinogenicity: N/A • Teratogenicity: N/A • Reproductive Toxicity: N/A • Mutagenicity: N/A • Synergis-

tic Products: N/A

Emergency First Aid Procedures:

Eyes: Flush with large amounts of water for 15 minutes. Seek medical attention immediately.

Skin: Wash skin with soap and water. If irritation occurs, seek medical attention.

Ingestion: Induce vomiting. Seek medical attention immediately giving full details of amount ingested and

toxicity.

Inhalation: Move to fresh air.

SECTION VI - Reactivity Data

Stability: Stable.

Incompatibility: Oxidizers, strong alkali.

Hazardous Decomposition Products: When heated to decomposition, it can emit toxic fumes of K₂O, SO_x

and I-.

Hazardous Polymerization: Will not occur.

Conditions to Avoid: Do not store near strong mineral acids or strong alkali.

SECTION VII - Spill or Leak Procedure

Steps to be taken in case material is released or spilled: Wear protective clothing as specified in Section VIII. If federal, state and local laws permit, flush to the sewer with large amounts of water.

Waste Disposal: If federal, state and/or local laws permit, flush to sewer with large amounts of water. Otherwise dispose of contaminated product and materials used in cleaning up the spill in a manner approved for this material. Consult proper federal, state and/or local regulatory agencies to ascertain proper disposal procedures.

SECTION VIII - Special Protection Information

Respiratory Protection (Specify Type): Should not be necessary under normal conditions.

Ventilation: Good local mechanical ventilation should be sufficient.

Protective Equipment:
Gloves: Impervious gloves.
Eyes: Wear protective goggles.

Other: As necessary to prevent skin contact. Eyewash facilities in vicinity of use.

SECTION IX - Special Precautions

Precautions to be taken in handling and storage: Do not store near strong mineral acids or strong alkalize. Wash thoroughly after use.

The information contained in this material safety data sheet is furnished without warranty of any kind. The user should consider this data a supplement to other information gathered and must make independent determination of suitability and completeness of information from this and other sources to assure proper use and disposal of this materials and the health and safety of employees and customers. This statement is incorporated as part of this Material Safety Data Sheet.