

8417 Chapin Industrial Drive
St. Louis, MO 63114
(314) 423-1919 800-325-4404
FAX: (314) 423-3914



Health	1
Flammability	0
Reactivity	0
Personal Protection	B

January 16, 2001

MATERIAL SAFETY DATA SHEET

SECTION I - General Information

Product Name: Trelux TL-50 Developer and Replenisher, Part A
Catalog Number: 55DE550, 55DE560, 55DE571, 50DE501
Formula: Aqueous Solution

SECTION II - Product and *Hazardous Ingredients Information

<u>Concentrate</u>	<u>CAS #</u>	<u>PERCENT</u>	<u>PEL</u>	<u>SARA</u> <u>RQ / TPQ</u>	
Potassium Carbonate	584-08-7	40-45	N/A	N/A	N/A
Potassium Sulfite	10117-38-1	1-5	N/A	N/A	N/A
Potassium Bromide	7758-02-3	<1	5 mg/m ³	N/A	N/A
*Potassium Hydroxide	1310-58-3	<1	N/A	N/A	N/A
*DTPA Na5	00014-00-12	1-5	N/A	N/A	N/A
Water	7732-18-5	N/A	N/A	N/A	N/A

Note: DTPA Na5 may contain up to 2% Trisodium Nitrilotriacetate Trisodium NTA (CAS # 5064-31-3) or Nitrilotriacetic acid NTA (CAS # 139-13-9) Both are listed as a Carcinogen by IARC NTP.

Working Solution

N/A

SECTION III - Physical Data

BOILING POINT: >212° F
VAPOR DENSITY (mmHg): ~0.6
SPECIFIC GRAVITY: 1.41
EVAPORATION RATE: N/A
APPEARANCE AND ODOR: Clear, colorless, and odorless.

VAPOR PRESSURE (mmHg): ~ 17.0
SOLUBILITY IN WATER: Complete
pH: ~ 11.70
PERCENT VOLATILE BY WEIGHT: ~59%

SECTION IV - Fire and Explosion Hazard Data

Flash Point: None
Flammable Limits: LEL: N/A **UEL:** N/A
Extinguishing Media: Use method appropriate for surrounding fire.
Special Fire Fighting Procedures: Use self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.
Unusual Fire and Explosions Hazards: None Known.

SECTION V - Health Hazard Data

TLV (ACGIH): Potassium Hydroxide - 2mg/m³(TWA), Potassium Bromide - 10 mg/m³.

Effects of Overexposure:

Inhalation: Vapor may cause irritation to nose and throat. May cause difficulty in breathing.
Eyes: Vapor causes irritation. Contact can cause severe burns.

Skin: Repeated and prolonged contact may cause irritation or allergic skin reaction.

Ingestion: Harmful if swallowed. May cause nausea and loss of consciousness. May cause burns to upper digestive tract.

Emergency First Aid Procedures:

Eyes: Flush with large amounts of water for 15 minutes. Seek medical attention immediately.

Skin: Wash skin with soap and water. If irritation occurs, seek medical attention.

Ingestion: If conscious, drink water or milk. **DO NOT induce vomiting.** Seek medical attention immediately, giving full details of amount ingested and toxicity.

Inhalation: Move to fresh air. Get medical attention if breathing becomes difficult.

Carcinogenicity: *See note above on Trisodium Nitrilotriacetate Trisodium NTA (CAS # 5064-31-3) •
Teratogenicity: N/A • Reproductive Toxicity: Trisodium Nitrilotriacetate Trisodium NTA (CAS # 5064-31-3) is known to the state of California to cause cancer and birth defects or other reproductive harm
• Mutagenicity: NA • Synergistic Products: N/A

SECTION VI - Reactivity Data

Stability: Stable.

Incompatibility: Strong acids.

Hazardous Decomposition Products: When heated to decomposition it emits CO₂. Contact with strong acids will create heat and release SO₂.

Hazardous Polymerization: Will not occur.

Conditions to Avoid: Do not store near strong acids.

SECTION VII - Spill or Leak Procedure

Steps to be taken in Case Material is Released or Spilled: Wear protective clothing as specified in Section VIII. If federal, state and local laws permit, flush to the sewer with large amounts of water.

Waste Disposal: If federal, state and/or local laws permit, flush to sewer with large amounts of water. Otherwise dispose of contaminated product and materials used in cleaning up the spill in a manner approved for this material. Consult proper federal, state and/or local regulatory agencies to ascertain proper disposal procedures.

SECTION VIII - Special Protection Information

Respiratory Protection (Specify Type): Should not be necessary under normal conditions.

Ventilation: Good local mechanical ventilation should be sufficient.

Protective Equipment:

Gloves: Impervious gloves.

Eyes: Wear protective goggles.

Other: As necessary to prevent skin contact. Eyewash facilities in vicinity of use.

SECTION IX - Special Precautions

Precautions to be taken in Handling and Storage: Do not store near strong acids. Do not store above 100° F. Wash thoroughly after use.

The information contained in this material safety data sheet is furnished without warranty of any kind. The user should consider this data a supplement to other information gathered and must make independent determination of suitability and completeness of information from this and other sources to assure proper use and disposal of this materials and the health and safety of employees and customers. This statement is incorporated as part of this Material Safety Data Sheet.

Health	1
Flammability	0
Reactivity	0
Personal Protection	B

November 7, 2000

MATERIAL SAFETY DATA SHEET

SECTION I - General Information

Product Name: Trelux TL-50 Developer and Replenisher, Part B
Catalog Number: 55DE550, 55DE560, 55DE571, 50DE502
Formula: Aqueous Solution

SECTION II - Product and *Hazardous Ingredients Information

<u>Concentrate</u>	<u>CAS #</u>	<u>PERCENT</u>	<u>PEL</u>	<u>SARA</u>	
				<u>RQ /</u>	<u>TPQ</u>
Hydroxylamine Sulfate	10039-54-0	15-20	N/A	N/A	N/A
Water	7732-18-5	N/A	N/A	N/A	N/A

Working Solution

N/A

SECTION III - Physical Data

BOILING POINT: >212° F
VAPOR DENSITY (mmHg): ~0.6
SPECIFIC GRAVITY: 1.12
EVAPORATION RATE: N/A
APPEARANCE AND ODOR: Clear, Colorless, and Odorless.

VAPOR PRESSURE (mmHg): ~ 17.0
SOLUBILITY IN WATER: Complete
pH: ~ 2.2
PERCENT VOLATILE BY WEIGHT: ~80%

SECTION IV - Fire and Explosion Hazard Data

Flash Point: None
Flammable Limits: LEL: N/A **UEL:** N/A
Extinguishing Media: Use method appropriate for surrounding fire.
Special Fire Fighting Procedures: Use self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.
Unusual Fire and Explosions Hazards: None Known.

SECTION V - Health Hazard Data

TLV (ACGIH): N/A

Effects of Overexposure:

Inhalation: Prolonged or excessive inhalation may result in headache and nausea. Expected to be a low hazard under normal conditions.

Eyes: Vapor may cause irritation. Contact will cause irritation and possible burns.

Skin: Repeated and prolonged contact may cause irritation.

Ingestion: Harmful if swallowed. Do not take internally. May cause nausea or loss of consciousness.

Carcinogenicity: N/A • **Teratogenicity:** N/A • **Reproductive Toxicity:** N/A • **Mutagenicity:** NA • **Synergistic Products:** N/A

Emergency First Aid Procedures:

Eyes: Flush with large amounts of water for 15 minutes. Seek medical attention.

Skin: Wash skin with soap and water. If irritation occurs, seek medical attention.

Ingestion: Drink water or milk and induce vomiting. Seek medical attention immediately giving full details of amount ingested and toxicity.

Inhalation: Move to fresh air. Get medical attention if breathing becomes difficult.

SECTION VI - Reactivity Data

Stability: Stable.

Incompatibility: BrF₃, Strong Alkali.

Hazardous Decomposition Products: When heated to decomposition it emits toxic fumes of SO_x. Sulfuric acid fumes may form in fires.

Hazardous Polymerization: Will not occur.

Conditions to Avoid: None Known.

SECTION VII - Spill or Leak Procedure

Steps to be taken in Case Material is Released or Spilled: Wear protective clothing as specified in Section VIII. Neutralize with sodium bicarbonate. If federal, state and local laws permit, flush to the sewer with large amounts of water.

Waste Disposal: If federal, state and/or local laws permit, flush to sewer with large amounts of water. Otherwise dispose of contaminated product and materials used in cleaning up the spill in a manner approved for this material. Consult proper federal, state and/or local regulatory agencies to ascertain proper disposal procedures.

SECTION VIII - Special Protection Information

Respiratory Protection (Specify Type): Should not be necessary under normal conditions.

Ventilation: Good local mechanical ventilation should be sufficient.

Protective Equipment:

Gloves: Impervious gloves.

Eyes: Wear protective goggles.

Other: As necessary to prevent skin contact. Eyewash facilities in vicinity of use.

SECTION IX - Special Precautions

Precautions to be taken in Handling and Storage: Do not store near strong alkali. Wash thoroughly after use.

The information contained in this material safety data sheet is furnished without warranty of any kind. The user should consider this data a supplement to other information gathered and must make independent determination of suitability and completeness of information from this and other sources to assure proper use and disposal of this materials and the health and safety of employees and customers. This statement is incorporated as part of this Material Safety Data Sheet.

8417 Chapin Industrial Drive
St. Louis, MO 63114
(314) 423-1919 800-325-4404
FAX: (314) 423-3914



Health	2
Flammability	0
Reactivity	0
Personal Protection	B

October 17, 2000

MATERIAL SAFETY DATA SHEET

SECTION I - General Information

Product Name: Trelux TL-50 Developer and Replenisher, Part C
Catalog Number: 55DE550, 55DE560, 55DE571, 50DE502
Formula: Aqueous Solution

SECTION II - Product and Hazardous Ingredients Information

<u>ITEM</u>	<u>CAS #</u>	<u>PERCENT</u>	<u>PEL</u>	<u>SARA</u> <u>RQ /TPQ</u>	
4-(N-Ethyl-N-2-hydroxyethyl)-2-methylene phenylene - diamine sulfate	25646-77-9	25-30	N/A	N/A	N/A
Sodium Metabisulfite	7681-57-4	5-10	N/A	N/A	N/A
Water	7732-18-5	N/A	N/A	N/A	N/A

Working Solution

N/A

SECTION III - Physical Data

BOILING POINT: >212° F
VAPOR DENSITY (mmHg): ~ 0.6
SPECIFIC GRAVITY: 1.15
EVAPORATION RATE: N/A
APPEARANCE AND ODOR: Reddish brown, sulfur dioxide odor.

VAPOR PRESSURE (mmHg): ~ 17.0
SOLUBILITY IN WATER: Complete
pH: ~ 2.0
PERCENT VOLATILE BY WEIGHT: ~ 62%

SECTION IV - Fire and Explosion Hazard Data

Flash Point: None
Flammable Limits: LEL: N/A **UEL:** N/A
Extinguishing Media: Use method appropriate for surrounding fire.
Special Fire Fighting Procedures: Use self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.
Unusual Fire and Explosions Hazards: None Known.

SECTION V - Health Hazard Data

TLV (ACGIH): Sulfur Dioxide - 2 ppm (TWA)

Effects of Overexposure:

Inhalation: Vapor may cause irritation to nose and throat. May cause difficulty in breathing.
Eyes: Vapor causes irritation. Contact can cause severe burns.
Skin: Repeated and prolonged contact may cause irritation or allergic skin reaction.
Ingestion: Harmful if swallowed. Can cause burns in upper digestive tract.

Emergency First Aid Procedures:

Eyes: Flush with large amounts of water for 15 minutes. Seek medical attention immediately.

Skin: Wash skin with soap and water. If irritation occurs, seek medical attention.

Ingestion: If conscious, drink water or milk. **DO NOT induce vomiting.** Seek medical attention immediately, giving full details of amount ingested and toxicity.

Inhalation: Move to fresh air. Get medical attention if breathing becomes difficult.

Carcinogenicity: N/A • **Teratogenicity:** N/A • **Reproductive Toxicity:** N/A • **Mutagenicity:** NA • **Synergistic Products:** N/A

SECTION VI - Reactivity Data

Stability: Stable.

Incompatibility: Mineral acids and strong alkalis.

Hazardous Decomposition Products: When heated to decomposition it emits toxic fumes of SO_x. Contact with strong acids will release SO₂.

Hazardous Polymerization: Will not occur.

Conditions to Avoid: Do not store near mineral acids and strong alkalis.

SECTION VII - Spill or Leak Procedure

Steps to be taken in Case Material is Released or Spilled: Wear protective clothing as specified in Section VIII. Neutralize with sodium bicarbonate. If federal, state and local laws permit, flush to the sewer with large amounts of water.

Waste Disposal: If federal, state and/or local laws permit, flush to sewer with large amounts of water. Otherwise dispose of contaminated product and materials used in cleaning up the spill in a manner approved for this material. Consult proper federal, state and/or local regulatory agencies to ascertain proper disposal procedures.

SECTION VIII - Special Protection Information

Respiratory Protection (Specify Type): An approved acid gas respirator is necessary when exposed to vapors.

Ventilation: Good local mechanical ventilation should be sufficient.

Protective Equipment:

Gloves: Impervious gloves.

Eyes: Wear protective goggles.

Other: As necessary to prevent skin contact. Eyewash facilities in vicinity of use.

SECTION IX - Special Precautions

Precautions to be taken in Handling and Storage: Do not store near mineral acids and strong alkalis. Do not store above 100° F. After use, wash hands with a non-alkaline hand cleaner.

The information contained in this material safety data sheet is furnished without warranty of any kind. The user should consider this data a supplement to other information gathered and must make independent determination of suitability and completeness of information from this and other sources to assure proper use and disposal of this materials and the health and safety of employees and customers. This statement is incorporated as part of this Material Safety Data Sheet.

8417 Chapin Industrial Drive
St. Louis, MO 63114
(314) 423-1919 (800) 325-4404
FAX : (314) 423-3914



Health	2
Flammability	0
Reactivity	0
Personal Protection	B

May 8, 2002

MATERIAL SAFETY DATA SHEET

SECTION I - General Information

Product Name: Film PAC C-41 RA Fixer
Catalog Number: 55FP475
Formula: Aqueous solution

SECTION II - Product and Hazardous Ingredients Information

<u>Item</u>	<u>Cas#</u>	<u>Percent</u>	<u>PEL</u>	<u>SARA RQ</u>	<u>SARA TPO</u>
Ammonium Thiocyanate	7783-18-8	25-30	N/A	N/A	N/A
Ammonium Thiocyanate	1762-95-4	10-15	N/A	N/A	N/A
Ammonium Bisulfite	17026-44-7	1-5	N/A	N/A	N/A
Water	7732-18-5	N/A	N/A	N/A	N/A

SECTION III - Physical Data

BOILING POINT: > 212°F
VAPOR DENSITY (mmHg): ~ 0.6
SPECIFIC GRAVITY: 1.24
PERCENT VOLATILE BY WEIGHT: ~ 45%
APPEARANCE AND ODOR: Clear light yellow color, slight ammonia odor.

VAPOR PRESSURE (mmHg): ~ 18
SOLUBILITY IN WATER: Complete
pH: > 6.6
EVAPORATION RATE: N/A

SECTION IV - Fire and Explosion Hazard Data

Flash Point: None
Flammable Limits: LEL: None UEL: None
Extinguishing Media: Use method appropriate for surrounding fire.
Special Fire Fighting Procedures: Use self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.
Unusual Fire and Explosions Hazards: When heated to decomposition, it can emit toxic fumes of ammonia and SO_x.

SECTION V - Health Hazard Data

TLV (ACGIH): N/A

Effects of Overexposure:

Inhalation: Expected to be a low hazard under normal conditions.
Eyes: Will cause irritation.
Skin: Repeated and prolonged contact may cause irritation.
Ingestion: Do not take internally. Harmful if swallowed. May cause nausea.

Carcinogenicity: N/A • Teratogenicity: N/A • Reproductive Toxicity: N/A • Mutagenicity: N/A • Synergistic Products: N/A

Emergency First Aid Procedures:

Eyes: Flush with large amounts of water for 15 minutes. Seek medical attention.

Skin: Wash skin with soap and water. If irritation occurs, call medical attention.

Ingestion: Induce vomiting. Seek medical attention immediately giving full details on amount ingested and toxicity.

Inhalation: Move to fresh air.

SECTION VI - Reactivity Data

Stability: Stable.

Incompatibility: Strong acids, strong alkalis.

Hazardous Decomposition Products: When heated to decomposition, it can emit toxic fumes of ammonia and SO_x. Contact with strong acids will release SO₂ and contact with strong alkalis will release ammonia.

Hazardous Polymerization: Will not occur.

Conditions to Avoid: Do not store near strong acids or strong alkalis.

SECTION VII - Spill or Leak Procedure

Steps to be Taken in Case Material is Released or Spilled: Wear protective clothing as specified in Section VIII. Neutralize with sodium bicarbonate. If federal, state and local laws permit, flush to the sewer with large amounts of water.

Waste Disposal: If federal, state and/or local laws permit, flush to sewer with large amounts of water. Otherwise dispose of contaminated product and materials used in cleaning up the spill in a manner approved for this material. Consult proper federal, state and/or local regulatory agencies to ascertain proper disposal procedures.

SECTION VIII - Special Protection Information

Respiratory Protection (Specify Type): If TLV or PEL limits are exceeded, use an appropriate respirator.

Ventilation: Good local mechanical ventilation should be sufficient.

Protective Equipment:

Gloves: Impervious gloves.

Eyes: Wear protective goggles.

Other: As necessary to prevent skin contact. Eyewash facilities in vicinity of use. Routine use of a non-alkaline type hand cleaner will minimize the possibility of an allergic skin reaction.

SECTION IX - Special Precautions

Precautions to be Taken in Handling and Storage: Do not store near strong acids or strong alkalis. Wash thoroughly after use.

The information contained in this material safety data sheet is furnished without warranty of any kind. The user should consider this data a supplement to other information gathered and must make independent determination of suitability and completeness of information from this and other sources to assure proper use and disposal of these materials and the health and safety of employees and customers. This statement is incorporated as part of this Material Safety Data Sheet.

8417 Chapin Industrial Drive
St. Louis, MO 63114
(314) 423-1919 (800) 325-4404
FAX : (314) 423-3914



Health	2
Flammability	0
Reactivity	0
Personal Protection	B

May 8, 2002

MATERIAL SAFETY DATA SHEET

SECTION I - General Information

Product Name: Film PAC CN-41 RA Odorless Bleach Replenisher
Catalog Number: 55FP475
Formula: Aqueous solution

SECTION II - Product and Hazardous Ingredients Information

<u>Item</u>	<u>Cas#</u>	<u>Percent</u>	<u>PEL</u>	<u>SARA RQ</u>	<u>SARA TPO</u>
Ferric Ammonium PDTA	111687-36-6	10-15	N/A	N/A	N/A
Proprietary	N/A	5-10	N/A	N/A	N/A
Ammonium Nitrate**	6484-52-2	1-5	N/A	N/A	N/A
Ammonium Bromide	12124-97-9	5-10	N/A	N/A	N/A
Water	7732-18-5	65-70	N/A	N/A	N/A

**May be subject to SARA section 313 reporting requirements

SECTION III - Physical Data

BOILING POINT: > 212°F
VAPOR DENSITY (m m Hg): ~ 0.6
SPECIFIC GRAVITY: 1.123
PERCENT VOLATILE BY WEIGHT: ~ 65%
APPEARANCE AND ODOR: Greenish/brown. Odorless.

VAPOR PRESSURE (m m Hg): ~ 18
SOLUBILITY IN WATER: Complete
pH: > 3.95
EVAPORATION RATE: N/A

SECTION IV - Fire and Explosion Hazard Data

Flash Point: None
Extinguishing Media: Media appropriate for surrounding fire.
Special Fire Fighting Procedures: Use self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.
Unusual Fire and Explosions Hazards: Fire or excessive heat may cause hazardous decomposition products.

Flammable Limits: LEL: None UEL: None

SECTION V - Health Hazard Data

TLV (ACGIH): N/A

Effects of Overexposure:

Inhalation: May cause irritation of respiratory tract. Expected to be a low hazard under normal conditions.
Eyes: Causes severe irritation and possible burns.
Skin: Causes severe irritation and possible burns.
Ingestion: Do not take internally. May cause severe irritation and possible burns to the upper digestive tract.

Carcinogenicity: N/A • Teratogenicity: N/A • Reproductive Toxicity: N/A • Mutagenicity: N/A • Synergistic Products: N/A

Emergency First Aid Procedures:

Eyes: Flush with large amounts of water for 15 minutes. Seek medical attention.

Skin: Wash skin with soap and water. If irritation occurs, seek medical attention.

Ingestion: Drink 1-2 glasses of water. Do Not induce vomiting. Seek medical attention immediately giving full details of amount ingested and toxicity.

Inhalation: Move to fresh air.

SECTION VI - Reactivity Data

Stability: Stable.

Incompatibility: Metals and strong oxidizers.

Hazardous Decomposition Products: Thermal decomposition may produce hydrogen bromide gas, ammonia and oxides of nitrogen.

Hazardous Polymerization: Will not occur.

Conditions to Avoid: Do not store near strong oxidizers.

SECTION VII - Spill or Leak Procedure

Steps to be Taken in Case Material is Released or Spilled: Wear protective clothing as specified in Section VIII.

If federal, state and local laws permit, flush to the sewer with large amounts of water.

Waste Disposal: If federal, state and/or local laws permit, flush to sewer with large amounts of water. Otherwise dispose of contaminated product and materials used in cleaning up the spill in a manner approved for this material. Consult proper federal, state and/or local regulatory agencies to ascertain proper disposal procedures.

SECTION VIII - Special Protection Information

Respiratory Protection (Specify Type): If TLV or PEL limits are exceeded, use an appropriate respirator.

Ventilation: Good local mechanical ventilation should be sufficient.

Protective Equipment:

Gloves: Impervious gloves.

Eyes: Wear protective goggles.

Other: As necessary to prevent skin contact. Eyewash facilities in vicinity of use. Routine use of a non-alkaline type hand cleaner will minimize the possibility of an allergic skin reaction.

SECTION IX - Special Precautions

Precautions to be Taken in Handling and Storage: Do not store or consume food, drink and tobacco in area. Do not store near strong oxidizers or metal containers. Wash thoroughly after use.

The information contained in this material safety data sheet is furnished without warranty of any kind. The user should consider this data a supplement to other information gathered and must make independent determination of suitability and completeness of information from this and other sources to assure proper use and disposal of these materials and the health and safety of employees and customers. This statement is incorporated as part of this Material Safety Data Sheet.

8417 Chapin Industrial Drive
 St. Louis, MO 63114
 (314) 423-1919 800-325-4404
 FAX: (314) 423-3914



Health	1
Flammability	0
Reactivity	0
Personal Protection	B

August 27, 1998

MATERIAL SAFETY DATA SHEET

SECTION I - General Information

Product Name: Trelux E.L.F. Stabilizer and Replenisher
Catalog Number: 55ST594, 55ST595, 55ST596, 55ST597, 55ST598
Formula: Aqueous Solution

SECTION II - Product and *Hazardous Ingredients Information

<u>Concentrate</u>	<u>CAS #</u>	<u>PERCENT</u>	<u>PEL</u>	<u>SARA</u> <u>RQ / TPQ</u>
* Hexamethylenetetramine	100-97-0	20-25	N/A	100#/500#
Isothiazoline Derivative	N/A	1-5	N/A	N/A N/A
Diethanolamine	111-42-2	1-5	3 ppm TWA	N/A N/A
Proprietary Ingredient	N/A	1-5	N/A	N/A N/A
Water	7732-18-5	70-75	N/A	N/A N/A
Working Solution				
* Hexamethylenetetramine	100-97-0	<1	N/A	100#/500#
Isothiazoline Derivative	N/A	<1	N/A	N/A N/A
Diethanolamine	111-42-2	<1	3 ppm TWA	N/A N/A
Proprietary Ingredient	N/A	<1	N/A	N/A N/A
Water	7732-18-5	99-100	N/A	N/A N/A

* Hexamethylenetetramine may liberate formaldehyde and ammonia vapors in an acid medium or upon decomposition.

SECTION III - Physical Data

Concentrate

BOILING POINT: >212° F VAPOR PRESSURE (mmHg): N/A
 VAPOR DENSITY(mmHg): N/A SOLUBILITY IN WATER: Complete
 SPECIFIC GRAVITY: 1.07 pH: ~ 9.15
 EVAPORATION RATE: N/A PERCENT VOLATILE BY WEIGHT: ~ 70 %
 APPEARANCE AND ODOR: Light yellow, odorless.

Working Solution

BOILING POINT: >212° F VAPOR PRESSURE (mmHg): same as water
 VAPOR DENSITY(mmHg): same as water SOLUBILITY IN WATER: Complete
 SPECIFIC GRAVITY: 1.000 pH: ~9.0
 EVAPORATION RATE: same as water PERCENT VOLATILE BY WEIGHT: ~ 99 %
 APPEARANCE AND ODOR: Light yellow, odorless.

SECTION IV - Fire and Explosion Hazard Data

Flash Point: N/A **Flammable Limits: LEL:** NA **UEL:** NA
Extinguishing Media: Use appropriate agent for surrounding fire.
Special Fire Fighting Procedures: Use self contained breathing apparatus and protective clothing to prevent contact with skin and eyes.
Unusual Fire and Explosions Hazards: Excessive heat may cause hazardous decomposition products.

SECTION V - Health Hazard Data

Effects of Overexposure:

Inhalation: Expected to be a low hazard under normal conditions.
Eyes: May cause irritation.
Skin: Repeated and prolonged contact may cause irritation.

Ingestion: Do not take internally. Harmful if swallowed. May cause irritation to upper digestive tract.

Emergency First Aid Procedures:

Eyes: Flush with large amounts of water for 15 minutes. Seek medical attention immediately.

Skin: Wash skin with soap and water. If irritation occurs, seek medical attention.

Ingestion: **DO NOT** induce vomiting. Give victim a glass of water only if conscious. Seek medical attention immediately giving full details of amount ingested and toxicity.

Inhalation: Move to fresh air. Get medical attention if symptoms are present.

TLV (ACGIH): Formaldehyde, 3/10 ppm (TLV-C). Ammonia, 25 ppm (TWA). Diethanolamine, 3 ppm (TWA).

PEL (OSHA): Formaldehyde, 0.75 ppm (TWA). Ammonia, 35 ppm (STEL). Diethanolamine, 3 ppm (TWA).

Carcinogenicity: Formaldehyde is a suspected carcinogen • **Teratogenicity:** Lungs; formaldehyde •

Reproductive Toxicity: N/A • **Mutagenicity:** Lungs; formaldehyde • **Synergistic Products:** N/A

SECTION VI - Reactivity Data

Stability: Stable.

Incompatibility: Strong oxidizers and strong acids.

Hazardous Decomposition Products: Combustion will produce carbon dioxide and possibly carbon monoxide. May liberate formaldehyde and ammonia vapors in an acid medium or upon decomposition.

Hazardous Polymerization: Will not occur.

Conditions to Avoid: Do not store near strong oxidizers or strong acids.

SECTION VII - Spill or Leak Procedure

Steps to be Taken in Case Material is Released or Spilled: Wear protective clothing as specified in Section VIII. If federal, state and local laws permit, flush to the sewer with large amounts of water.

Waste Disposal: If federal, state and/or local laws permit, flush to sewer with large amounts of water. Otherwise dispose of contaminated product and materials used in cleaning up the spill in a manner approved for this material. Consult proper federal, state and/or local regulatory agencies to ascertain proper disposal procedures.

SECTION VIII - Special Protection Information

Steps to be Taken in Case Material is Released or Spilled: Wear protective clothing as specified in Section VIII. If federal, state and local laws permit, flush to the sewer with large amounts of water.

Waste Disposal: If federal, state and/or local laws permit, flush to sewer with large amounts of water. Otherwise dispose of contaminated product and materials used in cleaning up the spill in a manner approved for this material. Consult proper federal, state and/or local regulatory agencies to ascertain proper disposal procedures.

SECTION VIII - Special Protection Information

Respiratory Protection (Specify Type): Should not be necessary under normal conditions.

Ventilation: Good local mechanical ventilation should be sufficient.

Protective Equipment:

Gloves: Impervious gloves.

Eyes: Wear protective goggles.

Other: As necessary to prevent skin contact. Eyewash facilities in vicinity of use. The routine use of a non-alkaline type hand cleaner will minimize the possibility of an allergic skin reaction. If formaldehyde is released, use OSHA standard 29 CFR 1910.1048 for specific details regarding personal protective equipment.

SECTION IX - Special Precautions

Precautions to be Taken in Handling and Storage: Do not store or consume food, drink or tobacco in area. Keep away from strong acids and oxidizing materials. Store above 40° F. Wash thoroughly after use.

The information contained in this material safety data sheet is furnished without warranty of any kind. The user should consider this data a supplement to other information gathered and must make independent determination of suitability and completeness of information from this and other sources to assure proper use and disposal of this materials and the health and safety of employees and customers. This statement is incorporated as part of this Material Safety Data Sheet.