



August 31, 1994

Health	1
Flammability	0
Reactivity	0
Personal Protection	B

Trebla
8417 Chapin Industrial Drive
St. Louis, MO 63114
Phone 1-800-325-4404

MATERIAL SAFETY DATA SHEET

SECTION I - General Information

Product Name: Trelux C-41 RA Fixer and Replenisher

Catalog Number: 55FX564, 55FX566, 55FX567

Formula: Aqueous Solution

SECTION II - Product and *Hazardous Ingredients Information

ITEM	CAS #	PERCENT	PEL	SARA	
				RQ	TPQ
Ammonium Thiosulfate	7783-18-8	35-40	N/A	N/A	N/A
Ammonium Thiocyanate	1762-95-4	1-5	N/A	N/A	N/A
Ammonium Sulfite	17026-44-7	1-5	N/A	N/A	N/A
Water	7732-18-5	55-60	N/A	N/A	N/A

SECTION III - Physical Data

BOILING POINT: > 212° F

VAPOR DENSITY(mmHg): N/A

SPECIFIC GRAVITY: ~1.18

EVAPORATION RATE: N/A

APPEARANCE AND ODOR: Clear, slight ammonia odor.

VAPOR PRESSURE (mmHg): ~17 @20°C

SOLUBILITY IN WATER: Complete

pH: ~9.5

PERCENT VOLATILE BY WEIGHT: ~60 %

SECTION IV - Fire and Explosion Hazard Data

Flash Point: None

Flammable Limits: LEL: N/A **UEL:** N/A

Extinguishing Media: Use method appropriate for surrounding fire.

Special Fire Fighting Procedures: Use self contained breathing apparatus and protective clothing to prevent contact with skin and eyes.

Unusual Fire and Explosions Hazards: When heated to decomposition, it can emit toxic fumes of ammonia, SO_x and CO_x.

SECTION V - Health Hazard Data

TLV (ACGIH): N/A

Effects of Overexposure:

Inhalation: Expected to be a low hazard under normal conditions.

Eyes: Will cause irritation.

Skin: Repeated and prolonged contact may cause irritation.

Ingestion: Do not take internally. Harmful if swallowed. May cause Nausea.

Carcinogenicity: N/A • **Teratogenicity:** N/A • **Reproductive Toxicity:** N/A • **Mutagenicity:** NA •

Synergistic Products: N/A

Emergency First Aid Procedures:

Eyes: Flush with large amounts of water for 15 minutes. Seek medical attention.

Skin: Wash skin with soap and water. If irritation occurs, seek medical attention.

Ingestion: Induce vomiting. Seek medical attention immediately giving full details of amount ingested and toxicity.

Inhalation: Move to fresh air.

SECTION VI - Reactivity Data

Stability: Stable.

Incompatibility: Strong acids, strong alkalis.

Hazardous Decomposition Products: When heated to decomposition, it can emit toxic fumes of ammonia SO_x and CO_x . Contact with strong acids will release SO_2 and contact with strong alkalis will release ammonia.

Hazardous Polymerization: Will not occur.

Conditions to Avoid: Do not store near strong acids or strong alkalis.

SECTION VII - Spill or Leak Procedure

Steps to be Taken in Case Material is Released or Spilled: Wear protective clothing as specified in Section VIII. If federal, state and local laws permit, flush to the sewer with large amounts of water.

Waste Disposal: If federal, state and/or local laws permit, flush to sewer with large amounts of water. Otherwise dispose of contaminated product and materials used in cleaning up the spill in a manner approved for this material. Consult proper federal, state and/or local regulatory agencies to ascertain proper disposal procedures.

SECTION VIII - Special Protection Information

Respiratory Protection (Specify Type): Should not be necessary under normal conditions.

Ventilation: Good local mechanical ventilation should be sufficient.

Protective Equipment:

Gloves: Impervious gloves.

Eyes: Wear protective goggles.

Other: As necessary to prevent skin contact. Eyewash facilities in vicinity of use.

SECTION IX - Special Precautions

Precautions to be Taken in Handling and Storage: Do not store near strong acids or strong alkalis. Wash thoroughly after use.

The information contained in this material safety data sheet is furnished without warranty of any kind. The user should consider this data a supplement to other information gathered and must make independent determination of suitability and completeness of information from this and other sources to assure proper use and disposal of this materials and the health and safety of employees and customers. This statement is incorporated as part of this Material Safety Data Sheet.